

Pro-Ject Xtension

Manual turntable with static or dynamic balanced 9" or 12" Ortofon tonearm and build in Pro-Ject Speed Box SE



(Picture shows Xtension/RS-309D)

Turntable

- Available finishes

Cherry



Apple



Olive



Black gloss



- A quiet running AC motor with a two-step metal pulley drives the platter's outside edge via a belt.
- Electronic speed change between 33 and 45 r.p.m.. Switching to 78 r.p.m. is done manually.
- The medium density fibre plinth rests on four individually height-adjustable magnetic field feet. A build in spirit level allows easy adjustment of the chassis.
- The resonance-optimised platter is a sandwich construction utilising a fine-balanced and damped aluminium platter weighing 5,7kg and a 4mm thick flat-ground layer of vinyl and a brass record puck.
- The magnet supported, inverted bearing uses a stainless-steel axle carrying a ceramic ball on which the ceramic bearing plate runs.
- Central metal block optimises centre of gravity and damps main bearing.
- External power supply avoids potential electro-mechanical interference.

Tonearms

Modell Xtension/AS-212S with static balanced 9" tonearm Ortofon AS-212S

Modell Xtension/AS-309S with static balanced 12" tonearm Ortofon AS-309S

Modell Xtension/AS-212D with dynamic balanced 9" tonearm Ortofon RS-212D

Modell Xtension/AS-309D with dynamic balanced 12" tonearm Ortofon RS-309D

Modell Xtension/without tonearm. Arm board for 9" and 12" tonearms

Dimensions W x H x D: With dust cover closed 550 x 250 x 450mm, dust cover open 550 x 550 x 560mm.

The manufacturer reserves the right to alter the technical specifications without notice.
The colours in the picture may differ slightly from the actual article due to inaccuracies in the printing process.