

THETA



IsoTek[®]
SMART Power

A 2U (89mm) high rack width component, offering full system control of connected electronics through RS232, LAN, Bluetooth and over WiFi with a Smartphone App. Theta features six UK (BS 1363), European Schuko or American 3-pin output sockets along with RS232 via traditional and USB ports, LAN Ethernet port for WiFi control and antenna supporting Bluetooth. Input power is via 16A IEC C19/20 connection. Theta also features a sophisticated circuit to remove both Differential and Common Mode mains noise from each output socket stopping mains noise cross contamination between connected electronics. Theta protects connected equipment up to 67500A.

- Name each outlet with connected electronics
- Turn on / off each outlet independently
- Remote reboot and sequential start-up
- Programmable delay times between each outlet upon start-up
- Control each outlet independently with date and time start-up
- Combine two or more units into named groups
- Manage power usage and overview power consumption
- Protection against power surges and voltage spikes
- Power cleaning network for each outlet and RFI reduction of 60dB
- Control through RS232, LAN, Bluetooth and over WiFi with a Smartphone App

SPECIFICATIONS

Output sockets:	6
Outlet socket style:	UK (BS 1363), EU Schuko, US 3-pin
Mains voltage:	100-240V / 50-60Hz
Amperage:	16A
Total (continuous) power:	3680W (230V) / 1840W (115V)
Protection rating:	67500A
Dimensions (mm):	448 x 305 x 89 (W x D x H)

Isotek[®]

SMART Power

© 2017 Audio Power Systems GmbH. All rights reserved.

Unauthorised copy or reproduction of any part of this booklet is prohibited and subject to prosecution.

Information contained in this brochure is correct at the time of printing, product improvements will take place from time to time.

