


LITTORA 200 OD SUB 12

Product Sheet

The OD Sub 12 subwoofer takes The Focal sound into your outdoor spaces! Its speaker driver with 12" (30cm) Iris IP cone delivers deep and powerful bass to your OD Sat 5 system. Its integrated transformer also makes it 70/100V compatible to cover large spaces with no loss of power. Plus, this subwoofer is IP55-certified to withstand adverse weather and extreme climates, so you can keep listening all year round. Available in Dark and Light finishes, it is designed to be partially buried to blend seamlessly into any outdoor space and surroundings.

Vent: resistant structure



5-Strand cable for 8Ω and 70/100V amplification

Key points


- Woofer with 12" (30cm) Iris IP cone: deep and powerful bass (400W)
- Adjustable vent height
- IP55-certified technical design (water and dust)
- Robust design
- Compatible with OD Sat 5 for a complete system
- System is perfect for pairing with OD Stone 8

Technical specifications

Type of speaker	Outdoor subwoofer
Speaker drivers	11 ³ / ₄ " (30cm) woofer with Iris IP cone
Bandwidth	40Hz - 120Hz
Impedance	6Ω
Minimal impedance	5Ω at 55Hz
Sensitivity	90dB
Power	100W RMS - 400W Peak
Recommended amp power 8Ω	50W - 300W
Temperature tolerance	-20° / 65°
IP rating	IP55
Dimensions (WxDxH)	15"x36 ¹ / ₄ "x22" (38x92x56cm)
Weight	41.89lbs (19kg)



Frequency response



Levels calculation table

Nominal sensitivity	90dB		
	1m	2m	5m
Power(8Ω)/Distance			
1W (2.83V)	90dB	84dB	76dB
20W (12.6V)	103dB	97dB	89dB
50W (20V)	107dB	101dB	93dB
100W (28.3V)	110dB	104dB	96dB