

Technical Specifications

Operation	manual
Drive System	belt-drive (flat belt around sub-platter)
Motor	servo-controlled DC motor
Speeds	33-1/3, 45 rpm
Speed Change	Electronic
Platter	12" / 0.9 kg (aluminium/acrylic)
Tonearm	THORENS® TP 90
Pick-up Cartridge	THORENS® TAS 267
Anti-skating (Bias)	by magnet
Automatic Shut-off	none
Power Supply	external plug-in power supply, 12 V DC/AC, 6 W min.
Dimensions	475 x 125 x 370 mm (W x H x D)
Weight	5.6 kg
Finish	MDF plinth with laquer in red, black or white (high gloss)
Scope of Delivery	power supply, dust cover (acrylic), RCA interconnects, stylus gauge, spirit level, cartridge alignment protractor

Technical Specifications

Operation	manual
Drive System	belt-drive (flat belt around sub-platter)
Motor	servo-controlled DC motor
Speeds	33-1/3, 45 rpm
Speed Change	Electronic
Platter	12" / 0.9 kg (aluminium/acrylic)
Tonearm	THORENS® TP 90
Pick-up Cartridge	THORENS® TAS 267
Anti-skating (Bias)	by magnet
Automatic Shut-off	none
Power Supply	external plug-in power supply, 12 V DC/AC, 6 W min.
Dimensions	470 x 125 x 430 mm (W x H x D)
Weight	4.7 kg
Finish	MDF plinth with laquer in red, black or white (high gloss)
Scope of Delivery	power supply, RCA interconnects, stylus gauge, spirit level, cartridge alignment protractor